

KLR650

Homepage

Contact Me

You must remove the "REMOVE-THIS" in my email address for it to work.

Links

Miscellaneous Info

D.I.Y. Tips

Grease 101

Technical Articles

A1 Brochure

Conversions

KLR650 FAQ

Painting Plastic

Forms

Maintenance Log

Shim Record Chart

Pictures

Corbin Saddle

Procedures in PDF

12v Waterproof Outlet

This is a hobby website dedicated to the Kawasaki KLR650 motorcycle. I make no claim concerning the accuracy of the procedures, nor do I guarantee the success of any work done using them. All users of the material found here are advised that there is no real or implied warranty associated in any way with the website content, and that all content available here is for use at your own risk.

Copyright © 2001 Mark's KLR Pages

All Rights Reserved

No copying or other redistribution by any method will be permitted without my express written permission.

MAGURA HYDRAULIC CLUTCH

The Magura Hydraulic Clutch is available at KLR650.COM

As is the case with all the procedures on this website, the pictures are ABOVE the text that they go with.



First, remove the clutch lever screws to release the clutch lever from the handlebars. Be careful that the small red adjustment "star" doesn't rub against the list switch assembly.

Acerbis Disk
Installation

Balancer
Adjustment

Brake Pads

Cam Chain
Timing

Carb Air Mixture

Carb Rain T-Mod

Decalifornication

Doohickey
Upgrade

Easy Lift

Fork Oil Change

Horn Upgrade

Hydraulic Clutch

JC Whitney
Trunk

Maier Woods Pro

Mirror Mount
Repair

Oil Screen
Cleaning

TIME-SERT

Radiator Cooling
Mod

Ramp Loading

Safety Switch
Bypass

Shark Fin
Installation

Shim Storage
Box



Now, the clutch safety interlock switch. The picture above shows the safety switch contacts.

Once you removed the 2 screws holding it to the stock lever, you will need to cut the copper plate on the switch. There are 3 wires: Green, Black with yellow and Blue. You do not use the green wire. You will need to attach the supplied terminals to the remaining wires and slip the supplied rubber boot over them as you attach them to the hydraulic clutch lever.

In the photos, the boot is installed and also removed, and with my finger, I am pointing to its location. I did not bother to install the clutch interlock switch and removed the wiring harness completely, but unplugging it from the connector behind the instrument panel.

Next, you must remove the clutch cable from the lever in order to pass the cable under the steering head.

Shim Value
Table

SuperBrace

Swingarm Maint

Torque Values

Tube Valve
Tools

Valve
Adjustment

Vista-Cruise
Lock

Water Pump
Seals

Wheel
Alignment



The picture above shows the attachment at the clutch actuator...

Once the clutch cable is removed from the lever, remove the bolt holding it at on the engine case and disconnect the clutch cable from the pivot. The easiest way to do this is to pull out the clutch pivot assembly and the long "spike" out of the clutch plate hole. (It only goes back in one way, so you can't mess it up.)



The picture above shows that the routing is the same as the original clutch cable...

With the hydraulic clutch assembly, pass the stainless steel braided line to the clutch "pivot" point at the engine casing. Attach the clutch cable to the "pivot" while it is removed from the engine, then insert the "spike" into the clutch plates hole (it can only go in one way).





The pictures above show the mirror attachment option, and how the choke control was mounted...

Attach the clutch lever to the handlebars. You will need to place it about an inch or so away from headlights assembly switch. Test the lever by pulling it in, and make sure the little red star shaped lever adjuster clears the switch assembly without rubbing on it. The little red star shaped knob allows you to adjust the lever's distance from the handlebar.

Done! Go for a test ride. The operation of the clutch is now effortless and you never have to adjust the clutch cable again. To me, this was a highly worthwhile upgrade.